

# 30-Gallon

The 30-gallon air compressor/generator conveniently fits on the back of a truck and supplies power to run air and electrical tools, perfect for the most remote jobs. Save space, save money and reduce load capacity with this combination unit.

**Compressor Pump:**

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

**Generator:**

- Brushless alternator
- Total harmonic distortion (THD) less than 6%
- 100% copper windings
- Comes standard with (2) 120V, 20A and (1) 240V, 20A receptacles

**Frame:**

- Powder coated ASME coded 30-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard

**Components:**

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16 1/2-inch fly wheel
- Quality pilot valve unloader

**Limited Warranties:**


- 1 year Mi-T-M engine
- 2 year alternator
- 2 year pump exchange (see page 66 for more information)
- 3 year Honda and Kohler engines
- 5 year Subaru engine

**Certifications:**

- ASME Boiler and Pressure Vessel Code - UM



AG2-SK14-30M shown with electric start option, AX-0071



## Two Stage – Gasoline

MODEL NUMBER	CFM @ 90 PSI	CFM @ 175 PSI*	MAX. OUTPUT	ALTERNATOR WATTAGE		RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
				CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD						
AG2-SH13-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	389cc Honda GX390 OHV	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SK14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	429cc Kohler CH440 OHV	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SM14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SR14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	404cc Subaru EX40 OHC	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.

\*Equipped with 150-PSI maximum rated regulator.

## 30-Gallon



AG2-SH13-30M shown with electric start option, AX-0019

## Accessories &amp; Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
70-0358	Engine oil drain extension	Honda, Kohler & Mi-T-M models	AX-0070	Battery tray, box and 2-ft. of cables included	All models
70-0380	Engine oil drain extension	AG2-SR14-30M	AX-0071	Electric start - battery, box and cables not included	AG2-SK14-30M
AW-6000-1002	Equipment cover	All models	AX-0072	Electric start - battery box and cables included, battery not included	AG2-SK14-30M
AX-0019	Electric start - battery, box and cables not included	AG2-SH13-30M	AX-0073	Electric start - battery, box and cables not included	AG2-SM14-30M
AX-0062	Electric start - battery, box and cables not included	AG2-SR14-30M	AX-0074	Electric start - battery box and cables included, battery not included	AG2-SM14-30M
AX-0063	Lifting hook	All models	AX-0075	Idle down - includes electric start - battery not included	AG2-SM14-30M
AX-0064	Electric start - battery box and cables included, battery not included	AG2-SH13-30M	IX-0001	Vibration isolator pads - <i>Isolators protect the unit from vibration during use; Recommended for models that are mounted in service truck applications</i>	All models
AX-0065	Electric start - battery box and cables included, battery not included	AG2-SR14-30M	IX-0055	Remote start/choke; 6-ft. wire extension for key switch; you will also need to order AX-0019	AG2-SH13-30M
AX-0068	Idle down - includes electric start - battery not included	AG2-SH13-30M			
AX-0069	Idle down - includes electric start - battery not included	AG2-SR14-30M			