

# 8-Gallon Base-Mount

The 8-gallon air compressor/generator is two pieces of equipment combined into one convenient machine. Use it to power lights, fans, run air tools and electric tools on the jobsite.

### Compressor Pump:

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

### Generator:

- Brushless alternator
- Total harmonic distortion (THD) less than 5%
- 100% copper windings
- Comes standard with (2) 120V, 20A and (1) 240V, 20A receptacles (Two-stage models)

### Frame:

- Powder coated 8-gallon twin tank receivers (Portable and stationary models)
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Flat-free tires (Portable models)

### Components:

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 12 or 16 1/2-inch fly wheel
- Quality pilot valve unloader

### Limited Warranties:

- 1 year Mi-T-M engine
- 2 year alternator
- 2 year pump exchange (see page 66 for more information)
- 3 year Honda and Kohler engines
- 5 year Subaru engine



AG2-SM14-08M1 shown with electric start option, AX-0073



## Single or Two Stage – Gasoline

PORTABLE	CFM @		MAX. OUTPUT	ALTERNATOR WATTAGE		RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	90 PSI	CFM @ PSI		CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD						
AG1-PH65-08M1	12.4	10.9 @ 125	1800 watts	600 watts	1600 watts	(2) NEMA 5-20R	196cc Honda GX200 OHV	Single stage	44.5x26x27.5in.	257 lb.	207 lb.
AG2-PH13-08M1	16.4	15.7 @ 175*	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	389cc Honda GX390 OHV	Two stage	52x28x34in.	450 lb.	375 lb.
AG2-PK14-08M1	16.4	15.7 @ 175*	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	429cc Kohler CH440 OHV	Two stage	52x28x34in.	450 lb.	375 lb.
AG2-PM14-08M1	16.4	15.7 @ 175*	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage	52x28x34in.	450 lb.	375 lb.
AG2-PS14-08M1	16.4	15.7 @ 175*	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	404cc Subaru EX40 OHC	Two stage	52x28x34in.	450 lb.	375 lb.

STATIONARY	CFM @		MAX. OUTPUT	ALTERNATOR WATTAGE		RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	90 PSI	CFM @ 175 PSI*		CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD						
AG2-SH13-08M1	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	389cc Honda GX390 OHV	Two stage	44x22x34in.	465 lb.	365 lb.
AG2-SK14-08M1	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	429cc Kohler CH440 OHV	Two stage	44x22x34in.	465 lb.	365 lb.
AG2-SM14-08M1	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage	44x22x34in.	465 lb.	365 lb.
AG2-SS14-08M1	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	404cc Subaru EX40 OHC	Two stage	44x22x34in.	465 lb.	365 lb.

BASE-MOUNT	CFM @		MAX. OUTPUT	ALTERNATOR WATTAGE		RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	90 PSI	CFM @ 175 PSI*		CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD						
AG2-SH13-B	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	389cc Honda GX390 OHV	Two stage	47x22x28in.	390 lb.	325 lb.
AG2-SK14-B	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	429cc Kohler CH440 OHV	Two stage	47x22x28in.	390 lb.	325 lb.
AG2-SM14-B	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage	47x22x28in.	390 lb.	325 lb.
AG2-SS14-B	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	404cc Subaru EX40 OHC	Two stage	47x22x28in.	390 lb.	325 lb.

\*Equipped with 150-PSI maximum rated regulator.

# 8-Gallon Base-Mount



AG2-PK14-08M1 shown with electric start option, AX-0071

## Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
70-0357	Engine oil drain extension	AG1-PH65-08M1	AX-0068	Idle down - includes electric start - battery not included	Two stage Honda models
70-0358	Engine oil drain extension	Two stage Honda, Kohler & Mi-T-M models	AX-0069	Idle down - includes electric start - battery not included	Subaru models
70-0380	Engine oil drain extension	Subaru models	AX-0071	Electric start - battery, box and cables not included	Kohler models
854-0093	Service truck mount kit - <i>recommended for models that are mounted in service truck applications</i>	Two stage portable & stationary models	AX-0072*	Electric start - battery box and cables included, battery not included	Kohler models
AW-6000-1002	Equipment cover	All models	AX-0073	Electric start - battery, box and cables not included	Mi-T-M models
AX-0019	Electric start - battery, box and cables not included	Two stage Honda models	AX-0074*	Electric start - battery box and cables included, battery not included	Mi-T-M models
AX-0028	Lifting hook	Two stage portable & stationary models	AX-0075	Idle down - includes electric start - battery not included	Mi-T-M models
AX-0062	Electric start - battery, box and cables not included	Subaru models	IX-0055	Remote start/choke; 6-ft. wire extension for key switch; you will also need to order AX-0019	Two stage Honda models
AX-0063	Lifting hook	Base-mount models			
AX-0064*	Electric start - battery box and cables included, battery not included	Two stage Honda models			
AX-0065*	Electric start - battery box and cables included, battery not included	Subaru models			

\*Note: Option cannot be mounted at the factory but can be shipped with the unit for custom mounting. Consult factory for more information.