


LANDA[®]
Kärcher Group

*Industrial Pressure Washers
...Built Right to Do the Job Right*

PE

*Portable, Electric-Powered,
Cold Water Pressure Washer*

- Up to 4.8 GPM, 3000 PSI
- Belt-Drive Pump with 7-Year Warranty
- Industrial Strength Baldor Motor
- Detergent Injection



◀ **Belt Pulley System** with notched V-belts and cast iron pulleys reduce belt slippage and offer longer belt life with cooler operation.

■ Insulated, fatigue-free, spring-loaded **Trigger Gun** with stainless steel, insulated, easy-grip **Spray Wand** make for easy point-and-shoot cleaning action.

■ Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.

■ Many **Safety Features**, including a thermal pump protector to prevent the buildup of excessive heat and a high-impact belt guard for operator protection.

■ Convenient **Hose/Gun Hanger** for carrying and accessing hose and gun.



■ 1¼-inch chrome-plated **Handles** on front and back for convenience in vehicle loading and unloading.

■ 50 feet of steel-wire braid **High Pressure Hose** rated for up to 6000 PSI with 24-inch **Hose Guard** for burst protection and **Swivel Crimp Fitting** for tangle-free handling of hose and trigger gun.

■ Durable pressure-trapping **Unloader** diverts water flow when trigger gun is not activated.

■ Four quick-couple **Nozzles** are made of hardened stainless steel and color-coded for easy selection of spray pattern: 0°, 15°, 25°, 40°.

■ Easy-to-attach **Detergent Injector** for easy application of soap.

■ Oil-bath, forged brass **Belt-Drive Pump** has a 7-year limited warranty on oil-end of pump.

■ Two spring-loaded **Rubber Pad Feet** absorb vibration for long life and keep the unit from "walking".

■ Water resistant **Electrical Box** for added safety and easy servicing.

■ Rugged 10-gauge steel **Chassis** is protected with all-weather-resistant epoxy powder coat paint.



■ Industrial-duty **Baldor Motors**, 2 to 10 HP, with full service factor provide unsurpassed reliability.

■ Four-ply, 13-inch tubed **Pneumatic Tires** make for easy maneuvering in any terrain (PE3-11024D uses 10-inch tires).

www.landa.com



WHY CHOOSE THE PE

The PE is the beefiest unit of our belt-drive, cold water pressure washer line offering ten models with cleaning power of up to 3000 PSI.

QUALITY: Only the highest quality components are used on the PE, including our tri-plex high-pressure pump with 7-year warranty, industrial-duty Baldor motor, durable steel frame with welded seams, and a stainless steel point-and-shoot wand for cleaning effectiveness. In addition to being certified to the rigid UL-1776 safety standards, the PE has a 24-inch hose guard for burst protection and tri-lingual operating instructions for owner liability assurance.

CONVENIENCE: There are a number of features that make the PE especially popular with users who seek to reduce their cleaning time. For instance, there are chrome-plated handles on both front and back for easy vehicle loading. The two leak-free, tubed pneumatic tires make for easy maneuvering in any terrain, and there are two shock absorbing, spring-loaded rubber feet to keep the PE from “walking” while in operation.



| Model # | Part # | GPM | PSI | Pump RPM | Motor HP | Volts | Phase | Amps | Ship Wt (lbs) |
|--------------|-------------|-----|------|----------|----------|-------|-------|------|---------------|
| PE2A-15024D* | 1.106-105.0 | 1.8 | 1500 | 1650 | 2.0 | 120 | 1 | 21 | 193 |
| PE3-11024D | 1.106-009.0 | 2.8 | 1000 | 1540 | 2.0 | 120 | 1 | 20 | 193 |
| PE4-20024A | 1.106-010.0 | 4.2 | 2000 | 900 | 6.2 | 230 | 1 | 27 | 285 |
| PE4-20024B | 1.106-011.0 | 4.2 | 2000 | 900 | 6.2 | 230 | 3 | 16 | 265 |
| PE4-20024C | 1.106-012.0 | 4.2 | 2000 | 900 | 6.2 | 460 | 3 | 8 | 266 |
| PE4-30024A | 1.106-013.0 | 3.5 | 3000 | 800 | 7.5 | 230 | 1 | 36 | 337 |
| PE4-30024B | 1.106-014.0 | 3.5 | 3000 | 800 | 7.5 | 230 | 3 | 21.5 | 290 |
| PE4-30024C | 1.106-015.0 | 3.5 | 3000 | 800 | 7.5 | 460 | 3 | 10.5 | 280 |
| PE5-30024B | 1.106-016.0 | 4.8 | 3000 | 1060 | 10.0 | 230 | 3 | 26.8 | 290 |
| PE5-30024C | 1.106-017.0 | 4.8 | 3000 | 1060 | 10.0 | 460 | 3 | 13.4 | 285 |

* PE2A-15024D comes equipped with Auto Start/Stop, two yellow nozzles, two green nozzles, and a variable pressure wand. Contact your local dealer for more details.

Distributed by: