

HOT

Portable, Electric-Powered, Diesel-Heated, Hot Water Pressure Washer

- Up to 3.5 GPM, 2000 PSI
- Heavy-Duty Motor
- Sch. 80 Heating Coil
- True Steam Model
- Easy to Service

■ **High-Pressure Pump** featuring three ceramic plungers and a forged brass head with 7-year warranty*, powered by heavy-duty **Legacy or Baldor Motor**.

■ High-heat aluminized steel inner wrap surrounds cold-rolled **Heating Coil** made of Schedule 80 steel pipe with five-year warranty.

■ **Stainless Steel Top Wrap** has unique design that allows access to the coil within minutes by simply removing six bolts.*

■ **Helpful Graphics and Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.

■ High-efficiency **Burner** is protected by a cover and mounted on the end for easy access.

■ **Adjustable Thermostat** for precise temperature control.

■ Quick-couple **Nozzle** is made of hardened stainless steel and mounted for ready access.

■ **Removable Panels** allow for easy access and servicing of pump, motor and unloader.

■ 36 ft. of high-grade **Electrical Cord** with ground fault circuit interrupter on all models for operator safety.

■ Conveniently located **Control Panel** with 3-position or rocker switch is housed in a water-resistant electrical enclosure.

■ Insulated, fatigue-free **Trigger Gun** with dual-lance **Variable Pressure Wand** provide remote change from low-pressure application of soap to high-pressure rinse.*

■ Easy-to-attach **Downstream Detergent Injector** for application of soap.

■ 50 ft. of steel-wire braid **High Pressure Hose** with guard for burst protection.*

■ **Many Safety Features**, including a rupture disk and thermal pump protector to prevent the buildup of excessive pressures or heat.

▶ **Optional Hose Reel and Lifting Bracket** with compact, easy-wind design for tangle-free handling of hose.



■ Two-ply, tubed **Pneumatic Tires** make for easy maneuvering in any terrain; safety brake prevents rolling.

▶ **Optional rust-free Float Tank** with stainless steel inlet filter, backflow protection and inlet detergent metering valve.



*HOT2-11026D and HOT2-15026D have axial pump with 1-year warranty, yellow painted mild-steel top coil wrap, and 30 ft. high pressure hose with straight-through insulated wand. HOT3-30036D Steamer has high limit switch, axial pump with 1-year warranty, and 50 ft. steam hose and wand.



WHY CHOOSE THE HOT

The HOT is the most economical choice of our electric-powered, diesel-heated hot water pressure washers featuring the heat-efficient horizontal coil. It is also the only line among those with a horizontal coil design that has a true steam cleaner, or steamer—the HOT3-30036D.

QUALITY: The HOT boasts many of the quality components of our hot water pressure washers, including a tri-plunger high-pressure pump with 7-year warranty (on most models), Schedule 80 heating coil made of 1/2-inch pipe and easy access to pump and motor.

PORTABILITY: All of the HOT models weigh less than 600 lbs. and are evenly balanced on four leak-free, tubed, pneumatic tires for easy maneuvering in any terrain. Waffle grips on the two steering bars add to the HOT's portability.

SAFETY: Certified to the rigid UL-1776 safety standards, the HOT also has many features that make it extremely safe, including motor thermal overload protection, rupture disk attached to the heating coil, thermal pump protector, flow-activated fuel shut-off switch, hose guard for burst protection, and Ground Fault Circuit Interrupter on all models.



**HOT3-30036D
Steamer**



HOT2-15026D shown with optional caster wheel kit

Model #	Part #	GPM	PSI	Pump	Pump RPM	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
HOT2-11026D	1.109-093.0	2.0	1000	Axial	3450	1.5	120	1	18	425
HOT2-15026D	1.109-094.0	1.9	1500	Axial	3450	2.0	120	1	20	428
HOT2-11024D	1.109-095.0	2.0	1000	Direct	1725	1.5	120	1	18	516
HOT2-15024D	1.109-096.0	1.9	1500	Direct	1725	2.0	120	1	20	529
HOT3-11024D	1.109-097.0	2.8	1000	Direct	1725	2.0	120	1	20	530
HOT4-20024A	1.109-098.0	3.5	2000	Belt	1350	5.0	230	1	25	561
HOT4-20024G	1.109-099.0	3.5	2000	Belt	1350	5.0	208	1	27	581
Extra-Hot Steamer (310° F):										
HOT3-30036D	1.109-100.0	2.0	300	Axial	3450	1.5	120	1	12	519

Distributed by:

Field Installed Options & Accessories

- 8.750-487.0 Landa Kärcher Group Pivot Reel (100' capacity)
- 8.750-477.0 Landa Kärcher Group Non-Pivot Reel (100' capacity)
- 8.917-541.0 Hose Reel Platform with E-Zee Reel & Plumbing (holds 100' of 3/8" hose, not included)*
- 8.917-522.0 Hose Reel Platform Only*
- 8.917-525.0 Wheel Kit (2 casters)
- 8.917-506.0 Float Tank with Inlet Detergent Metering Valve
- 9.802-283.0 Hour Meter (machine pre-wired for easy installation)

* Should not be used as a lifting rack on the MHC